


RoHS Compliant





CIRCUIT DIAGRAM





P.C.B LAND PATTERN





SPECIFICATIONS

Rating	50mA , 12V DC
Contact Resistance	70mΩ Max.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Insulation Resistance	100MΩ Min.
Operating Force	150 ± 50gf
Operating Life	10,000 cycles
Travel	1.0 ± 0.2mm

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
F	SPRING STRIP	1	SUS	
E	TERMINAL	1	PHOSPHOR BRONZE	Ag plated
D	CLIP	1	QBE2	Ag plated
C	COVER	1	PHOSPHOR BRONZE	Ag plated
B	BASE	1	NYLON	Black
A	SLIDER	1	NYLON	White

ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 10/24/23	MAT'L		TITLE	SWITCH
CHECKED BY: Jacky Chen	DATE 10/24/23	FINISH		MODLE	SMT SLIDE SWICTH
APPROVED BY: Tony Kao	DATE 10/24/23	SCALE	1 : 1	DWG NO.	SS-B92AP-W-S463 SIZE A4
		SHEET NO.	1 of 1	PART NO.	SS-B92AP-W-S463 VER A1