









RoHS Compliant


P.C.B LAYOUT
TOP VIEW

Model NO.	DC-073DS-1.3
SCHEMATIC	3/5 (+) 4 2 (−)



SPECIFICATION

1.Rating ：DC 30V , 2.0A；
2.Contact resistance：≤30mΩ；
3.Insulation resistance：≥100MΩ；
4.Withstand voltage：500VAC ；
5.Insertion and extraction force：3-30N;
6.life test：5,000 cycles。



RECOMMENDED PLUG

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	CONTACT FOOT	1	BRASS	Ag-Plating
5	PIN	1	H59	Ni-Plating
4	CONTACT FOOT	1	BRASS	Ag-Plating
3	CURVE PIECE	1	BRASS	Ag-Plating
2	SPRING	1	PHOSPHOR BRONZE	Ag-Plating
1	HOUSING	1	PA9T	

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	更新圖面	Jack	081722
4	更新料號	Jack	080621
3	更新料號	Jack	101817
2	更新為A0版	Jack	042117
1	更新圖面	Jack	021617

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 30 ±0.3; Above 30 ~ 50 ±0.4; Above 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 08/17/22	MAT'L	
CHECKED BY: Jacky Chen	DATE 08/17/22	FINISH	
APPROVED BY: Tony Kao	DATE 08/17/22	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	DC JACK		
DWG NO.	DC-073DS-1.3-S124	SIZE	A4
PART NO.	DC-073DS-1.3-S124	VER	R5