



NOTES:

MATERIAL:

- 1.1 HOUSING: LCP & PA9T
- 1.2 CONTACT: PHOSPHOR BRONZE
- 1.3 SHELL: BRASS

FINISH:

- 2.1 CONTACT: PLATED GOLD IN MATING AREA ;
GOLD PLATED ON SOLDER BALLS ;
NICKEL UNDER PLATED OVERALL
- 2.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER

3.SPECIFICATION:

- 3.1 RATING: 30V DC/AC , 1.0A
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC
- 3.3 CONTACT RESISTANCE: 30 mΩ MAX.
- 3.4 INSULATION RESISTANCE: 500 MΩ MIN.
- 3.5 TEMPERATURE RANGE: -20°C ~ +60°C
- 3.6 WATERPROOF LEVER: IP45

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 11/16/17
DATE: 11/16/17
DATE: 11/16/17

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO USB 5PIN SMT(AB)TYPE 沉板 平口防水型 板上H:1.4mm
SCALE	1 : 1	DWG NO.	MRUSB-5AB-WP4-S235
SHEET NO.	1 of 1	PART NO.	MRUSB-5AB-WP4-S235
		SIZE	A4
		VER	A0

2	更新為A0版	Jack	111617
1	新增WATERPROOF LEVER	Jack	090717
ITEM NO.	DESCRIPTION	DRAWN	DATE