

















P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:

1.Current Rating: 0.5 Amperes

2.Contact Resistance: 50 mΩ Max

3.Dielectric Withstanding Voltage: AC 100 V

4.Insulation Resistance: 100 MΩ Min

5.Operating Temperature: -25˚C ~ 65˚C

Material:

1.Housing: High Temperature Thermal Plastics,UL 94V-0

2.Contact: Phosphor Bronze

3.Shell: Phosphor Bronze

Finish:

1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall

2.Shell: Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3˚

3RD. ANGEL'S | UNITS | MM

DRAWN BY: Jack Lu	DATE 06/23/15	MAT'L	
CHECKED BY: Jacky Chen	DATE 06/23/15	FINISH	
APPROVED BY: Tony Kao	DATE 06/23/15	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR		
MODLE	MINI USB AB 型 前插後貼無柱		
DWG NO.	MUSB-10P-SD1-S165	SIZE	A4
PART NO.	MUSB-10P-SD1-S165	VER	R