


SBC-240S-31x-S271


鍍層厚度 :


Blank : 1u"
2 : 15u"
3 : 30u"















A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

RoHS Compliant



P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:

1.Rating: 3.0A

2.Contact Resistance: 40 mΩ Max

3.Insulation Resistance: 100 MΩ Min

4.Withstanding Voltage: 100V AC

Material:

1.Housing: LCP

2.Contact: C18140

3.Shell: SUS

Finish:

1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall

2.Shell: Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE
6	更新Contact材質	Jack	021623
5	更新Contact材質	Jack	010423
4	更新PCB LAYOUTR及新增零件背面圖	Jack	010821
3	新增尺寸	Jack	052520
2	新增插入深度尺寸	Jack	052020
1	更新SPEC	Jack	041420

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 02/16/23	MAT'L	
CHECKED BY: Jacky Chen	DATE 02/16/23	FINISH	
APPROVED BY: Tony Kao	DATE 02/16/23	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR		
MODLE	USB 3.1 TYPE C PIN 腳長1.2mm		
DWG NO.	SBC-240S-31x-S271	SIZE	A4
PART NO.	SBC-240S-31x-S271	VER	R6