



RoHS Compliant

| | |
|---|---|
| (Number of Conductors) N | X |
| (Pitch) P | 0.50mm |
| (Total Pitch) Pt | X |
| (Total Length) L | X |
| (Film Length) IL | X |
| (Margin Width) M | X |
| (Total Width) W | X |
| (Strip Length) S1 | X |
| (Strip Length) S2 | X |
| (Stiffener) B1 | X |
| (Stiffener) B2 | X |
| (Slanting) A1 | X |
| (Slanting) A2 | X |
| (Terminal thickness) t | X |
| (Thickness) T | X |

| 規格 (Spec) | 0.5×X×X×D1 (X/X/X/X) (0.035×0.3) (0.06+0.06)UL20624 | | |
|---|---|---|---|
| 4 | 補强板 (Connecting) | 0.225 (深藍色) | |
| 3 | 上絕緣膠 (Top Insulation) | 0.06無鹵素皮膜 (白/印字white/printed) | 白色絕緣膠 綠色印字 |
| 2 | 下絕緣膠 (Under Insulation) | 0.06無鹵素皮膜 (白white) | |
| 1 | 導體 (Conductor) | 0.035×0.3 (鍍錫Tin plating) | |
| ITEM | DESCRIPTION | SPECIFICATION | REMARK |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|---|---|---|---|

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

| | | DATE |
|---|---|---|
| DRAWN BY: | Jack Lu | 11/27/15 |
| CHECKED BY: | Jacky Chen | 11/27/15 |
| APPROVED BY: | Tony Kao | 11/27/15 |

| | | | |
|---|---|---|---|
| MAT'L | | TITLE | FFC CABLE |
| FINISH | | MODLE | FFC CABLE |
| SCALE | 1 : 1 | DWG NO. | FD11-xxx-S281 |
| SHEET NO. | 1 of 1 | PART NO. | FD11-xxx-S281 |

SIZE A4 | VER R