RoHS Compliant

DIMENSIONS



SCHEMATIC



P.C.B MOUNTING PATTERN







Model No.	X(mm)
SS-12D01-G2	2mm
SS-12D01-G3	3mm
SS-12D01-G4	4mm
SS-12D01-G5	5mm
SS-12D01-G6	6mm
SS-12D01-G7	7mm
SS-12D01-G8	8mm
SS-12D01-G9	9mm

SPECIFICATIONS

Rating	0.3A 50V DC
FUNCTION	1P2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	200gf ± 80gf
Operating Life	10,000 cycle

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
5	CONTACT(CLIP)	1	BRASS	Ag-Plated
4	TERMINAL	3	BRASS	Ag-Plated
3	TERMINAL BASE	1	PHENOL IC RESIN	Natural
2	FRAME	1	SPCC	Ni-Plated
1	KNOB	1	POM	Black

ITEM NO.	DESCRIPTION	DRAWN	DATE
6	更新圖面樣式	Jack	101515
5	更新MODLE	Jack	052915
4	新增SPEC	Jack	111914
3	更新3.9mm的尺寸爲4.0mm	Jack	111414
2	新增3.9mm的尺寸	Jack	111214
1	更新尺寸及材質	Jack	031714

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS | MM

DRAWN BY: Jack Lu	DATE 10/15/15	MAT'L		TITLE	SWITCH
CHECKED BY: Jacky Chen	DATE 10/15/15	FINISH		MODLE	SLIDE SWITCH 1P2T 端子腳 L:4.8mm
APPROVED BY: Tony Kao	DATE 10/15/15	SCALE	1 : 1	DWG NO.	SS-12D01-Gx-S191
		SHEET NO.	1 of 1	PART NO.	SS-12D01-Gx-S191

SIZE A4 | VER A6