


RoHS Compliant







SCHEMATIC (NON-SHORTING)



P.C.B MOUNTING PATTERN
(BOTTOM VIEW)





Model No.	X(mm)
SS-22H06-G2	2mm
SS-22H06-G3	3mm
SS-22H06-G4	4mm
SS-22H06-G5	5mm
SS-22H06-G6	6mm
SS-22H06-G7	7mm
SS-22H06-G8	8mm
SS-22H06-G9	9mm

SPECIFICATIONS

Rating	DC 50V 0.3A
Circuit	2P - 2T
Timing	Non - Shorting
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	300 ± 100gf
Operating Life (cycles)	10,000

NO	PART NAME	MATERIAL	Q'TY	FINISHING
6	SPRING PLATE	STAINLESS STEEL	4	NATURAL
5	CONTACT CAP	PHOSPHOR BRONZE	2	AG-CLAD
4	TERMINAL	PHOSPHOR BRONZE	12	AG PLATED OVER NI PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL	1	NI PLATED
1	KNOB	POM	1	BLACK

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	102215

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 10/22/15	MAT'L		TITLE	SWITCH
CHECKED BY: Jacky Chen	DATE 10/22/15	FINISH		MODLE	SLIDE SWITCH
APPROVED BY: Tony Kao	DATE 10/22/15	SCALE	1 : 1	DWG NO.	SS-22H06-Gx SIZE A4
		SHEET NO.	1 of 1	PART NO.	SS-22H06-Gx VER R1