





P.C.B LAND PATTERN






CIRCUIT DIAGRAM

MODEL	X
SS-D45	2.0 mm
SS-D45A	4.0 mm





SPECIFICATIONS

Rating	0.3A 6V DC
Insulation Resistance	50MΩ Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100mΩ Max.
Operating Force	200 ± 50gf
Operating Life	10,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	6	PHOSPHOR BRONZE	Ag plated
D	CLIP	2	Be-Cu	Ag plated
C	COVER	1	SUS	
B	CASE	1	PA46	Black
A	SLIDER	1	PA46	Black

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新材質及Insulation Resistance	Jack	050615
2	更新CLIP材質	Jack	061614
1	更新爲A0版	Jack	060414

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 05/06/15	MAT'L	
CHECKED BY: Jacky Chen	DATE 05/06/15	FINISH	
APPROVED BY: Tony Kao	DATE 05/06/15	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH
MODLE	SLIDE SWICTH
DWG NO.	SS-D45x-B-S246
PART NO.	SS-D45x-B-S246

SIZE A4 VER A2