






P.C.B LAYOUT MOUNTING PATTERN





SPECIFICATIONS

Current rating : 1.0A AC , DC
Voltage rating : 100V AC , DC
Temperature rating : -25˚C ~ +85˚C
Insulation resistance : 500MΩ min.
Withstand voltage : 500V AC/minute
Contact resistance : 20mΩ/Max
Material:
Housing : Nylon 6T, UL94V-0
Pin : Brass / Tin-plated
Contact : Phosphor Bronze

PART NO.	Dimensions	
	A	B
WF-1500VS02	1.50	4.30
WF-1500VS03	3.00	5.80
WF-1500VS04	4.50	7.30
WF-1500VS05	6.00	8.80
WF-1500VS06	7.50	10.30
WF-1500VS07	9.00	11.80
WF-1500VS08	10.50	13.30
WF-1500VS09	12.00	14.80

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新圖面	Jack	010413

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°
3RD. ANGEL'S
UNITS MM

DRAWN BY: Jack Lu	DATE 01/04/13	MAT'L	
CHECKED BY: Jacky Chen	DATE 01/04/13	FINISH	
APPROVED BY: Tony Kao	DATE 01/04/13	SCALE	1 : 1
		SHEET NO.	1 of 1

TITLE	CONNECTOR		
MODLE	WAFER 1.5 SMT 180度		
DWG NO.	WF-1500VSxx-S208	SIZE	A4
PART NO.	WF-1500VSxx-S208	VER	R1