



SPECIFICATION

- 1. Rating : DC 12V 1.0A
- 2. Contact resistance: $\leq 50m\Omega$
- 3. Insulation resistance: $\geq 100M\Omega$
- 4. Withstand voltage: 500VAC
- 5. Insertion and extraction force: 3-30N
- 6. life test: 5,000 cycles

⑦ Terminal 6	⑥	1	Phosphor Bronze	Gold flash on contact area, gold flash plated on solder tail Area, all over nickel plated
⑥ Terminal 5	⑤	1	Phosphor Bronze	
⑤ Terminal 4	④	1	Phosphor Bronze	
④ Terminal 3	③	1	Phosphor Bronze	
③ Terminal 2	②	1	Phosphor Bronze	
② Terminal 1	①	1	Phosphor Bronze	
① Housing		1	PA10T	Black
NO.	DESCRIPTION	QTY	MATERIAL	REMARK

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	07/10/23	FINISH	MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-5416D-S458
Jacky Chen	07/10/23	SHEET NO.	PART NO.	PJ-5416D-S458
APPROVED BY:	DATE			SIZE
Tony Kao	07/10/23	1 of 1		A4
				VER
				R

ITEM NO.	DESCRIPTION	DRAWN	DATE