




P.C.B LAYOUT
TOP VIEW




SCHEMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A ;
2. Contact resistance : ≤30mΩ ;
3. Insulation resistance : ≥100MΩ ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-20N;
6. life test : 5,000 cycles °



⑧	COAT	1	PHOSPHOR BRONZE	Ni-Plating
⑦	HOUSING	1	PBT	
⑥	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
⑤	SPRING PIECE	1	SUS	Ag-Plating
④	CURVE PIECE	1	BRASS	Ag-Plating
③	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
②	SPRING PIECE	1	SUS	Ag-Plating
①	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	06/18/19		MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-D3043B-S124
Jacky Chen	06/18/19	1 : 1	PART NO.	PJ-D3043B-S124
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	06/18/19			

ITEM NO.	DESCRIPTION	DRAWN	DATE