



**SCHEMATIC**

**SPECIFICATION**

- 1. Rating : DC 30V, 3.0A
- 2. Contact resistance :  $\leq 50m\Omega$
- 3. Insulation resistance :  $\geq 100M\Omega$
- 4. Dielectric Withstanding Voltage : 500V AC

**MATERIAL**

HOUSING : TEMPERATURE PLASTIC  
 COVER : TEMPERATURE PLASTIC  
 CONTACT : COPPER ALLOY(Au Plated)

1	新增PCB LAYOUT尺寸	Jack	011918
ITEM NO.	DESCRIPTION	DRAWN	DATE

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5 ±0.2	3RD. ANGEL'S	UNITS	MM
	Above 5 ~ 15 ±0.3			
	Above 15 ~ 30 ±0.4			
	Above 30 ~ 50 ±0.5			
	Angle ±0.3°			

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	01/19/18			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK 防水型
Jacky Chen	01/19/18			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-WP1001HS-1.3-S377
Tony Kao	01/19/18	1 : 1	PART NO.	DC-WP1001HS-1.3-S377
		SHEET NO.	1 of 1	
				SIZE A4
				VER R1