


02 Comm.



SCHEMATIC

**SPECIFICATIONS:**

CONTACT RATING : 3 AMPS @ 120 V AC or 28 V DC.  
 1 AMPS @ 250 V AC or 0.4VA AMPS @ 20V AC OR DC  
 ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.  
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 VDC  
 100 mA , for both silver and gold plated contacts.  
 INSULATION RESISTANCE : 1,000 MΩ min  
 DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.  
 OPERATING TEMPERATURE : -30°C to 130°C

**MATERIALS:**

CASE : Dially phthalate (DAP)(UL-94V-0)  
 ACTUATOR : Nylon.  
 HOUSING : Stainless steel.  
 TERMINAL/CONTACT : Brass , with silver or gold plated.  
 or gold over silver  
 SWITCH SUPPORT : Brass , tin plated.

Model No.	TYPE		
DS-10	ON	NONE	ON
DS-11	ON	OFF	ON
Tem. Comm.	2-1	OPEN	2-3

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	04/13/16			
CHECKED BY:	DATE	FINISH	MODLE	SLIDE SWITCH 端子截齊
Jacky Chen	04/13/16			
APPROVED BY:	DATE	SCALE	DWG NO.	DS-1xA4
Tony Kao	04/13/16	1 : 1		
		SHEET NO.	PART NO.	DS-1xA4
		1 of 1		
				SIZE A4
				VER R2