








DIMENSIONS



CIRCUIT DIAGRAM



P.C.B LAYOUT MOUNTING PATTERN



HEIGHT

MODEL	H(mm)
TS-A01NH-x-S138	4.3
TS-A01NHA-x-S138	5.0

SPECIFICATIONS

Rating	DC 12V 50mA Max.				
Contact Resistance	100mΩ Max.				
Travel	0.25 ± 0.10 mm				
Operating Force	0 100±30gf	1 130±30gf	2 160±50gf	3 250±50gf	4 320±50gf
Operating Life (cycles)	50,000		30,000		

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	04/23/14		MODLE	TACT SWITCH
CHECKED BY:	DATE	FINISH	DWG NO.	TS-A01NHx-x-S138
Jacky Chen	04/23/14		PART NO.	TS-A01NHx-x-S138
APPROVED BY:	DATE	SCALE	SHEET NO.	1 of 1
Tony Kao	04/23/14	1 : 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增Operating Force選項4	Jack	042314