

RoHS Compliant


# MRUSB-5B-RV4x-S331


SHELL鍍層:


| |
|---|
| TN |
| NI |










P.C.B LAYOUT MOUNTING PATTERN

NOTES:

MATERIAL:

1.1 HOUSING: PA10T,UL94V-0 ,Black

1.2 CONTACT: BRASS

1.3 SHELL: SUS

Finish:

2.1 Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls
Nickel under plated overall

2.2 Shell: Nickel under Plated surface layer or
Tin under Plated surface layer

3.SPECIFICATION:

3.1 RATING: 30V AC , 1.8 A MAX

3.2 DIELECTRIC WITHSSTANDING VOLTAGE: 250 VAC

3.3 CONTACT RESISTANCE: 30 mΩ MAX.

3.4 INSULATION RESISTANCE: 100 MΩ MIN.

3.5 TEMPERATURE RANGE: -30°C ~ +85°C

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|---|---|---|---|
| 7 | 更新pcb layout | Jack | 120220 |
| 6 | 新增PIN編號 | Jack | 071818 |
| 5 | 更新尺寸 | Jack | 031417 |
| 4 | 更新為A0版 | Jack | 011717 |
| 3 | 新增pcb layout尺寸 | Jack | 052716 |
| 2 | 更新材質 | Jack | 030916 |
| 1 | 更新SPEC | Jack | 012616 |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S | UNITS MM

| | | | |
|---|---|---|---|
| DRAWN BY: Jack Lu | DATE 12/02/20 | MAT'L | |
| CHECKED BY: Jacky Chen | DATE 12/02/20 | FINISH | |
| APPROVED BY: Tony Kao | DATE 12/02/20 | SCALE 1 : 1 | SHEET NO. 1 of 1 |

| | |
|---|---|
| TITLE | CONNECTOR |
| MODLE | MICRO USB 反向平口 外殼4 腳插板 (PH:7.7-5.3mm) |
| DWG NO. | MRUSB-5B-RV4x-S331 |
| PART NO. | MRUSB-5B-RV4x-S331 |
| SIZE | A4 |
| VER | A2 |