










PCB Layout(Pattern Side)













Specification :

1. Rating :12 VAC/DC max. 2 VDC min. 10mA AC/DC max. 10μA DC min.
2. Contact Resistance : 200mΩ Max
3. Insulation Resistance :100MΩ Min (DC100V)
4. Withstand Voltage :AC500V(50-60Hz) for 1 minute
5. Bounce Time:≤5msec (at 16 in/sec. actuation speed)
6. Operation Force :50±15gf
7. Pressure Point Force :60±15gf
8. Pretravel:2.0mm±0.4mm
9. Total travel:4.0+0/-0.3mm
10. Operating Life :50,000,000 Cycles(min)
11. Protection class: IP40





Circuit Diagran

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Follower	———	1	POM	White	———
⑦	Base	———	1	Nylon	Black	———
⑥	contact	———	2	Silver alloy	Brushing Gold	———
⑤	Spring	———	1	Stainless Steel	———	———
④	Cover	———	1	Nylon	Black	———
③	Keystroke	———	1	POM	Blue	———
②	Terminal	———	1	Brass	Plating Nickel	———
①	Reed	———	1	Copper Alloy	———	———

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新MODLE	Jack	121615

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 12/16/15	MAT'L	
CHECKED BY: Jacky Chen	DATE 12/16/15	FINISH	
APPROVED BY: Tony Kao	DATE 12/16/15	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	Keyboard Switch / Blue Shaft		
DWG NO.	KS-01C-50-S105	SIZE	A4
PART NO.	KS-01C-50-S105	VER	R1