






PRODUCT IMAGE



P.C.B MOUNTING



SPECIFICATIONS:

CONTACT RATING : 1 AMPS @ 120 V AC or 28 V DC.
0.4 AMPS @ 20 V AC or DC
ELECTRICAL LIFE : 30,000 make-and-break cycles at full load.
CONTACT RESISTANCE : 20 mΩ max. initial @ 2-4 VDC
100 mA , for both coin silver and gold plated contacts.
INSULATION RESISTANCE : 1,000 MΩ min
DIELETRIC STRENGTH : 1,000 V RAM @ sea level.
OPERATING TEMPERTURE : -30°C to 130°C

MTAERIALS:

CASE : Dially phthalate (DAP)(UL-94V-0).
PLUNGER : Thermoplastic polyester-black.
BUSHING : Brass , nickel plated.
HOUSING : Stainless steel.
TERMINAL/CONTACT : Brass , witch silver or gold plated.
or gold over silver
SWITCH SUPPORT : Brass , tin plated.

Model No.	TYPE	
AS-04	ON	MOM
Tem. Comm.	2-1	2-3

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Frank Wu	11/07/11			
CHECKED BY:	DATE	FINISH	MODLE	Toggle PUSH SWITCH
Jacky Chen	11/07/11			
APPROVED BY:	DATE	SCALE	DWG NO.	AS-04
Tony Kao	11/07/11	1 : 1	PART NO.	AS-04
		SHEET NO.	1 of 1	