




PRODUCT IMAGE

SCHEMATIC



02 Comm.
1 3

SPECIFICATIONS:

CONTACT RATING : 3 AMPS @ 120 V AC or 28 V DC.

1.5 AMPS @ 250 V AC or 0.4 AMPS@20V AC OR DC

ELECTRICAL LIFE : 30,000 make-and-break cycles at full load.

CONTACT RESISTANCE : 20 mΩ max. initial @ 2-4 VDC

100 mA , for both coin silver and gold plated contacts.

INSULATION RESISTANCE : 1,000 MΩ min

DIELETRIC STRENGTH : 1,000 V RAM @ sea level.

OPERATING TEMPERTURE : -30°C to 130°C

MTAERIALS:

CASE : Dially phthalate (DAP)

BUSHING : Brass , nickel plated.

HOUSING : Stainless steel.

TERMINAL/CONTACT : Brass , silver plated.

SWITCH SUPPORT : Brass , Tin plated.

Model No.	Switching Position		
DS-40T1B1A1	ON	NONE	OFF
DS-41T1B1A1	ON	NONE	ON
DS-42T1B1A1	ON	OFF	ON
DS-43T1B1A1	ON	NONE	(ON)
Term Comm.	2- 3	OPEN	2- 1

CONTACT

建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
DATE: 10/27/21

CHECKED BY: Jacky Chen
DATE: 10/27/21

APPROVED BY: Tony Kao
DATE: 10/27/21

MAT'L	TITLE	SWITCH
FINISH	MODLE	Toggle SWITCH
SCALE	DWG NO.	DS-4xT1B1A1
SHEET NO.	PART NO.	DS-4xT1B1A1
1 of 1		

SIZE
A4
VER
R1