



Knob Height

MODEL	L(mm)
TS-A02MV	3.15
TS-A02 MVA	3.85
TS-A02 MVB	5.85
TS-A02 MVC	6.15
TS-A02 MVD	8.35
TS-A02 MVE	6.85

SPECIFICATIONS

Rating	DC 12V 50mA	
Contact Resistance	100mΩ Max.	
Travel	0.25 ± 0.1mm	
Operating Force	2-160 ± 50gf	3-250 ± 50gf
Operating Life (cycles)	100,000	

5	Contact	Phosphor Bronze	1	Ag PLATED
4	TERMINAL	C2680	4	Ag PLATED
3	CASE	PBT	1	BLACK
2	KNOB	PA66	2	BLACK
1	COVER	SPCC	1	Ni PLATED
NO	PARTS	MATFRIAL	QTY	FINISHING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	04/24/15			
CHECKED BY:	DATE	FINISH	MODLE	TACT SWITCH
Jacky Chen	04/24/15			
APPROVED BY:	DATE	SCALE	DWG NO.	TS-A02MVx-x-S064
Tony Kao	04/24/15	1 : 1	PART NO.	TS-A02MVx-x-S064
		SHEET NO.	1 of 1	SIZE A4
				VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增材質Contact	Jack	042415
1	新增尺寸	Jack	070113