
















RoHS Compliant

SCHEMATIC

PJ-2706D	PJ-2704D	PJ-2705D
		



PCB LAYOUT MOUNTING PATTERN
TOP VIEW



SPECIFICATION

1.Rating ：DC 30V , 1.0A
2.Contact resistance：≤30mΩ
3.Insulation resistance：≥100MΩ
4.Withstand voltage：500VAC
5.Insertion and extraction force：3-20N
6.life test：5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
⑦	HOUSING	1	PA9T	
⑥	6# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
⑤	5# CONTACT FOOT	1	SUS	Ag-Plating
④	4# CONTACT FOOT	1	BRASS	Ag-Plating
③	3# CONTACT FOOT	1	BRASS	Ag-Plating
②	2# CONTACT FOOT	1	SUS	Ag-Plating
①	1# CONTACT FOOT	1	SUS	Ag-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新爲A0版	Jack	012417
1	更新電路選項	Jack	051616

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 01/24/17	MAT'L	
CHECKED BY: Jacky Chen	DATE 01/24/17	FINISH	
APPROVED BY: Tony Kao	DATE 01/24/17	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-270xD-S125	SIZE	A4
PART NO.	PJ-270xD-S125	VER	A0