






RoHS Compliant


MODEL NO.	PJ-2966DT1	PJ-2965ADT1	PJ-2965BDT1	PJ-2964DT1
SCHEMATIC				




A DETAIL COPLANARITY

✳ MATERIAL

TERMINAL 1 : PHOSPHOR BRONZE
TERMINAL 2 : PHOSPHOR BRONZE
TERMINAL 3 : PHOSPHOR BRONZE
TERMINAL 4 : PHOSPHOR BRONZE
TERMINAL 10 : PHOSPHOR BRONZE
TERMINAL 11 : PHOSPHOR BRONZE
HOUSING : PA6T
TAPE : POLYMIDE





RECOMMENDED
SOLDER PAD LAYOUT

SPECIFICATION

1.Rating : DC 12V 1.0A
2.Contact resistance : ≤50m Ω
3.Insulation resistance : ≥100M Ω (DC500V)
4.Withstand voltage : 500VAC
5.Insertion and extraction force : 3-30N
6.life test : 5,000 cycles

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新爲A0版	Jack	110514

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 11/05/14	MAT'L	
CHECKED BY: Jacky Chen	DATE 11/05/14	FINISH	
APPROVED BY: Tony Kao	DATE 11/05/14	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-296xDT1	SIZE	A4
PART NO.	PJ-296xDT1	VER	A0