









Internal construction

RoHS Compliant

PJ-3525N



SPECIFICATION

1.Rating ：DC 30V 1.0A


2.Contact resistance：≤100mΩ

3.Insulation resistance：≥100MΩ


4.Withstand voltage：500VAC

5.Insertion and extraction force：3-25N

6.life test：5,000 cycles



PCB LAYOUT



NUT

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
⑪	NUT	1	H59	Ni-Plating
⑩	SPRING-5	1	72A	Ni-Plating
⑨	SPRING-3	1	72A	Ni-Plating
⑧	SOCKET	1	H59	Ni-Plating
⑦	COVER	1	PC	Transparent
⑥	HOUSING	1	PA66	Black
⑤	TERMINAL-5	1	BRASS	Ag-Plating
④	TERMINAL-4	1	BRASS	Ag-Plating
③	TERMINAL-3	1	BRASS	Ag-Plating
②	TERMINAL-2	1	BRASS	Ag-Plating
①	TERMINAL-1	1	BRASS	Ag-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	110315
1	更新材質	Jack	091815

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 11/03/15	MAT'L	
CHECKED BY: Jacky Chen	DATE 11/03/15	FINISH	
APPROVED BY: Tony Kao	DATE 11/03/15	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-3525N-S258	SIZE	A4
PART NO.	PJ-3525N-S258	VER	R2