



**SPECIFICATION**

1. Rating : DC 12V 1.0A
2. Contact resistance :  $\leq 50m\Omega$
3. Insulation resistance :  $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

**\*MATERIAL**

TERMINAL 1 : PHOSPHOR BRONZE  
 TERMINAL 2 : PHOSPHOR BRONZE  
 TERMINAL 3 : PHOSPHOR BRONZE  
 TERMINAL 4 : PHOSPHOR BRONZE  
 HOUSING : PA6T

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	Above 5 ~ 15 ±0.3	Above 15 ~ 30 ±0.4	Above 30 ~ 50 ±0.5	Angle ±0.3°
	3RD. ANGEL'S		UNITS	MM	

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	06/29/16		MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-5114D
Jacky Chen	06/29/16	1 : 1	PART NO.	PJ-5114D
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	06/29/16			
				SIZE A4
				VER R1