








P.C.B LAYOUT MOUNTING PATTERN
(TOP VIEW)




ø3.50mm 3 POLE PLUG



MODEL NO.	PJ-3733
SCHEMATIC	

SPECIFICATION

- Rating : DC 30V 0.5A ;
- Contact resistance : $\leq 30m\Omega$;
- Insulation resistance : $\geq 100M\Omega$;
- Withstand voltage : 500VAC ;
- Insertion and extraction force : 3-20N
- life test : 5,000 cycles .



④	HOUSING	1	PBT	
③	SPRING	1	Phosphor Bronze	Sn-Plating
②	SPRING	1	Phosphor Bronze	Sn-Plating
①	CONTACT FOOT	1	Brass	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	06/20/17	FINISH	MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-3733-S124
Jacky Chen	06/20/17	1 : 1	PART NO.	PJ-3733-S124
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	06/20/17			



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

ITEM NO.	DESCRIPTION	DRAWN	DATE
----------	-------------	-------	------