









P.C.B LAYOUT
TOP VIEW



Ø3.50mm 3 POLE PLUG




SCHEMATIC



SPECIFICATION

- 1.Rating : DC 30V 0.5A ;
- 2.Contact resistance : $\leq 30\text{m}\Omega$;
- 3.Insulation resistance : $\geq 100\text{M}\Omega$;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-20N;
- 6.life test : 5,000 cycles °



⑧	COAT	1	PHOSPHOR BRONZE	Ni-Plating
⑦	HOUSING	1	PBT	
⑥	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
⑤	SPRING PIECE	1	SUS	Ag-Plating
④	CURVE PIECE	1	BRASS	Ag-Plating
③	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
②	SPRING PIECE	1	SUS	Ag-Plating
①	CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	06/18/19		MODLE	PHONE JACK
CHECKED BY:	DATE	FINISH		
Jacky Chen	06/18/19		SCALE	1 : 1
APPROVED BY:	DATE	SHEET NO.	PART NO.	PJ-D3043B-S124
Tony Kao	06/18/19	1 of 1		

SIZE
A4
VER
R