





RoHS Compliant

P.C.B LAYOUT
TOP VIEW



ø3.50mm 4 POLE PLUG



SCHEMATIC









SPECIFICATION

1. Rating ：DC 30V 0.5A
2. Contact resistance：≤30mΩ
3. Insulation resistance：≥100MΩ
4. Withstand voltage：500VAC
5. Insertion and extraction force：3-30N
6. life test：5,000 cycles。

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
7	HOUSING	1	PA9T	
6	6# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
5	5# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
4	4# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
3	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
2	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating
1	1# CONTACT FOOT	1	PHOSPHOR BRONZE	Ag-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新材質和SCHEMATIC選項	Jack	041122
2	新增插入示意圖	Jack	060817
1	更新為A0版	Jack	031317

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED：Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 04/11/22	MAT'L	
CHECKED BY: Jacky Chen	DATE 04/11/22	FINISH	
APPROVED BY: Tony Kao	DATE 04/11/22	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-389xD-S124	SIZE	A4
PART NO.	PJ-389xD-S124	VER	R3