








CIRCUIT DIAGRAM



P.C.B LAYOUT MOUNTING PATTERN





SPECIFICATIONS

Rating	DC 12V 50mA Max.							
Contact Resistance	100 mΩ Max.							
Travel	1.30± 0.1 mm							
Operating Force	1	120 ± 30gf	2	180 ± 50gf	3	250 ± 50gf	4	320 ± 50gf
Operating Life (cycles)	100,000							80,000

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增Operating Force:320 ± 50gf	Jack	092618

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 09/26/18	MAT'L	
CHECKED BY: Jacky Chen	DATE 09/26/18	FINISH	
APPROVED BY: Tony Kao	DATE 09/26/18	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	TACT SWITCH		
DWG NO.	TS-A32USA-x-S138	SIZE	A4
PART NO.	TS-A32USA-x-S138	VER	R1