






SBC-060P-20x-S165

鍍層厚度 :

Blank : 1u"
2 : 15u"
3 : 30u"



P.C.B. LAYOUT



A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B7	DN2
A6	DP1	B6	DP2
A7	DN1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

SPECIFICATIONS

Electrical:

- Rating: 20 V, 3.0 A
- Dielectric Withstand Voltage: 100V AC
- Contact Resistance: 40 mΩ Max
- Insulation Resistance: 100 MΩ Min

Mechanical:

- Connector Mate and Unmate Force
 - Mate force: 5~20 N
 - Unmate force: 8~20 N

Material:

- Housing: LCP
- Contact: Phosphor Bronze
- Shell: SUS

Finish:

- Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- Shell: Nickel under Plated surface layer

5	更新端子鍍層	Jack	122324
4	新增尺寸	Jack	121624
3	更新圖面	Jack	120524
2	更新材質和鍍層	Jack	110524
1	更新Rating	Jack	040324
ITEM NO.	DESCRIPTION	DRAWN	DATE

**建倚科技股份有限公司**
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	12/23/24	FINISH		MODLE	USB 3.1 側插母座 6 PIN
CHECKED BY:	DATE	SCALE	1 : 1	DWG NO.	SBC-060P-20x-S165
Jacky Chen	12/23/24	SHEET NO.	1 of 1	PART NO.	SBC-060P-20x-S165
APPROVED BY:	DATE				
Tony Kao	12/23/24				
					SIZE A4
					VER R5