


P.C.B LAYOUT

MODEL NO.	TS-A05V	TS-05VAJ	TS-A05VA	TS-05VQ	TS-05VB	TS-A05VC	TS-A05VD
H (mm)	3.15	3.35	3.85	4.85	5.85	6.85	8.35
φ A	3.50	3.30	3.40	3.30	3.30	3.30	3.0

SPECIFICATIONS

Rating	DC 12V 50mA Max.		
Contact Resistance	100mΩ Max.		
Travel	0.25 ± 0.1mm		
Operating Force	2 160 ± 50gf	3	250 ± 50gf
Operating Life (cycles)	100,000	80,000	



CIRCUIT DIAGRAM

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	新增選項	Jack	091120
3	新增選項	Jack	110719
2	更新圖面	Jack	031419
1	更新圖面	Jack	083013

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	09/11/20		MODLE	TACT SW 支架高 :11.25mm
CHECKED BY:	DATE	FINISH	SCALE	1 : 1
Jacky Chen	09/11/20		DWG NO.	TS-A05Vx-x-S138
APPROVED BY:	DATE	SHEET NO.	PART NO.	TS-A05Vx-x-S138
Tony Kao	09/11/20	1 of 1		

SIZE A4
 VER R4