


RECOMMENDED PLUG



P.C.B LAYOUT
TOP VIEW

SPECIFICATION

1. Rating : DC 12V, 3.0A ;
2. Contact resistance : $\leq 30m\Omega$;
3. Insulation resistance : $\geq 100M\Omega$;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-20N
6. life test : 5,000 cycles .

MODEL NO.	DC-S060-1.3
SCHEMATIC	4 (+)
	3
	2 (-)

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
⑥	STOPPER	1	SUS	N/A
⑤	CONTACT FOOT	1	BRASS	Ag-Plating
④	PIN	1	BRASS	Ni-Plating
③	CURVE PIECE	1	BRASS	Ag-Plating
②	SPRING	1	PHOSPHOR BRONZE	Ag-Plating
①	HOUSING	1	PA9T	

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	07/17/23		MODLE	DC JACK
CHECKED BY:	DATE	FINISH	SCALE	1 : 1
Jacky Chen	07/17/23		DWG NO.	DC-S060-1.3-S124
APPROVED BY:	DATE	SHEET NO.	PART NO.	DC-S060-1.3-S124
Tony Kao	07/17/23	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新尺寸	Jack	071723
2	更新PCB LAYOUT尺寸	Jack	081222
1	更新圖面樣式和鍍層	Jack	121119

SIZE A4
VER R3