





SPECIFICATIONS

- Rating : DC 30V , 5.0A
- Contact resistance : $\leq 30m\Omega$
- Insulation resistance : $\geq 100M\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-20N
- life test : 5,000 cycles

Model No.	DC-D099-x
SCHEMATIC	 3  4 (1, 2)
CENTER PIN	$\phi 2.00$ mm $\phi 2.50$ mm

8	SPLIT WASHER	1	IRON	Ni-Plating
7	NUT	1	BRASS	Ni-Plating
6	COVER	1	PBT	
5	HOUSING	1	PBT (BLACK)	
4	SPRING	1	PHOSPHOR BRONZE	Sn-Plating
3	PIN	1	BRASS	Ni-Plating
2	CONTACT FOOT	1	BRASS	Sn-Plating
1	COAT	1	BRASS	Ni-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	07/17/20			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	07/17/20			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-D099-x-S124
Tony Kao	07/17/20	1 : 1		
		SHEET NO.	1 of 1	PART NO. DC-D099-x-S124
				SIZE A4
				VER R1