






HDMI PIN ASSIGNMENT			
PIN	SIGNAL TYPE	11	TMDS Clock Shield
1	TMDS Data2+	12	TMDS Clock−
2	TMDS Data2 Shield	13	CEC
3	TMDS Data2−	14	Utility
4	TMDS Data1+	15	SCL
5	TMDS Data1 Shield	16	SDA
6	TMDS Data1−	17	DDC/CEC Ground
7	TMDS Data0+	18	+5V Power
8	TMDS Data0 Shield	19	Hot Plug Detect
9	TMDS Data0−		
10	TMDS Clock+		











RECOMMENDED P.C.B. LAYOUT
TOP VIEW

NOTE:

1.MATERIAL:
- 1.1 HOUSING: LCP, BLACK
- 1.2 CONTACT: BRASS
- 1.3 SHEEL: BRASS

2.PLATING :
- 2.1 CONTACT: PLATED GOLD IN MATING AREA ;
  TIN PLATED ON SOLDER BALLS ;
  NICKEL UNDER PLATED OVERALL
- 2.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER

3.MECHANICAL:
- 3.1 INSERTION FORCE: 4.5 Kgf MAX
- 3.2 WITHDRAWAL FORCE: 1.0 ~ 4.0 Kgf

4.ELECTRICAL:
- 4.1RATING: 40V,0.5A
- 4.2 CONTACT RESISTANCE: 30 mΩ Max
- 4.3 INSULATION RESISTANCE: 100MΩ Min
- 4.4 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC / minute
- 4.5 OPERATING TEMPERATURE: -25°C~ 85°C

5.LIFE: 10,000 CYCLES

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	新增LIFE	Jack	051123
2	新增PIN定義	Jack	092922
1	更新PCB LAYOUT尺寸	Jack	092222

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

		DATE
DRAWN BY:	Jack Lu	05/11/23
CHECKED BY:	Jacky Chen	05/11/23
APPROVED BY:	Tony Kao	05/11/23

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	HDMI2.1 側插殼銅殼2 K腳 2直腳 腳長 2.3
SCALE	1 : 1	DWG NO.	HD2-19PF-P1-S297 SIZE A4
SHEET NO.	1 of 1	PART NO.	HD2-19PF-P1-S297 VER R3