



- SPECIFICATION**
- 1.Contact resistance : $\leq 50m\Omega$
 - 2.Insulation resistance : $\geq 100M\Omega$
 - 3.Withstand voltage : 250VAC
 - 4.Insertion and extraction force : 3-30N
 - 5.life test : 5,000 cycles

ITEM	DESCRIPTIONs	MATERIAL	FINISH	Q'TY
⑩	DUMMY PIN	STAINLESS STEEL	—	1
⑨	SEPARATOR	PA9T	BLACK	1
⑧	M5_CONTACT	PHOSPHOR BRONZE	Au: GOLD FLASH Ni	1
⑦	MQ_SHUNT	PHOSPHOR BRONZE		1
⑥	MP_CONTACT	PHOSPHOR BRONZE		1
⑤	M4_CONTACT	PHOSPHOR BRONZE		1
④	M1_CONTACT	PHOSPHOR BRONZE		1
③	M6_CONTACT	PHOSPHOR BRONZE		1
②	MS_SHELL	PHOSPHOR BRONZE	Ni	1
①	P1_HOUSING	PA9T	BLACK	1

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新日期樣式	Jack	080825
3	更新樣式	Jack	051525
2	更新樣式	Jack	060623
1	更新樣式和材質和鍍層	Jack	111722

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5	± 0.2
Above 5 ~ 15	± 0.3
Above 15 ~ 30	± 0.4
Above 30 ~ 50	± 0.5
Angle	$\pm 0.3^\circ$

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	08/08/25			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	08/08/25			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-S3R2A7-S214
Tony Kao	08/08/25	1 : 1		
		SHEET NO.	PART NO.	PJ-S3R2A7-S214
		1 of 1		

SIZE	A4
VER	R4