



Note:

- 1: Material :
Plunger: C3604
HOUSING: PA46
- 2: Plating :
Plunger: 3u" Au over 50~120u" Ni
- 3:Electrical :
Rated Current & Voltage: DC 5V;500MA
Contact Resistance: 50 mohm Max. at working height.
Has Good waterproof and dustproof performance ,the protection level is IP 65

				建倚科技股份有限公司 CONTACT TECHNOLOGY CORP.			DRAWN BY: Jack Lu		DATE: 07/11/24	MATL	TITLE: CONNECTOR		
							CHECKED BY: Jacky Chen		DATE: 07/11/24			FINISH	MODLE: POGO PIN 防水型 IP65
				TOLERANCE UNLESS OTHERWISE STATED :		Up to 5 ±0.2 Above 5 ~ 15 ±0.3 Above 15 ~ 30 ±0.4 Above 30 ~ 50 ±0.5 Angle ±0.3	3RD. ANGEL'S	UNITS	MM	SCALE: 1 : 1	DWG NO. PGC-W208055-3P-S410	VER: R	
ITEM NO.	DESCRIPTION	DRAWN	DATE			APPROVED BY: Tony Kao	DATE: 07/11/24	SHEET NO. 1 of 1	PART NO. PGC-W208055-3P-S410				