


RoHS Compliant

P.C.B. LAYOUT

SBC-160P5-20x-S410

鍍層厚度 :

Blank : 1u"
2 : 15u"
3 : 30u"

A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	D+	B7	D-
A7	D-	B6	D+
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	GND	B1	GND

SPECIFICATIONS

Electrical:

1.Rating: 5.0 A

2.Dielectric Withstand Voltage: 100V AC

3.Contact Resistance: 40 mΩ Max

4.Insulation Resistance: 100 MΩ Min

Mechanical:

1.Connector Mate and Unmate Force

1.1 Mate force: 5~20 N

1.2 Unmate force: 8~20 N

MATERIAL:

1.Housing: LCP

2.Contact: C7025

3.Shell: SUS

Finish:

1.Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall

2.Shell: Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	更新圖面	Jack	033126
4	新增PCB LAYOUT尺寸	Jack	122223
3	新增尺寸	Jack	122123
2	新增尺寸	Jack	100323
1	新增尺寸	Jack	092123

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 03/31/26	MAT'L	
CHECKED BY: Jacky Chen	DATE 03/31/26	FINISH	
APPROVED BY: Tony Kao	DATE 03/31/26	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR
MODLE	USB TYPE C 2.0 側插母座 16 PIN CH4.58
DWG NO.	SBC-160P5-20x-S410
PART NO.	SBC-160P5-20x-S410
SIZE	A4
VER	R5