




SCHEMATIC



P.C.B MOUNTING PATTERN



Model No.	X(mm)
SS-12F20-G2	2mm
SS-12F20-G3	3mm
SS-12F20-G4	4mm
SS-12F20-G5	5mm
SS-12F20-G6	6mm
SS-12F20-G7	7mm
SS-12F20-G8	8mm
SS-12F20-G9	9mm

SPECIFICATIONS

Rating	DC 50V 0.5A
Circuit	1P - 2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	180gf ± 80gf
Operating Life (cycles)	10,000

6	CONTACT	1	BRASS	Ag-Plated
5	SPRING	1	STEEL	Natural
4	TERMINAL	3	BRASS	Ag-Plated
3	BASE	1	PHENOLIC RESIN	Natural
2	FRAME	1	STEEL	Ni-Plated
1	NOB	1	POM	Black
NO.	DESCRIPTION	QTY	MATERIAL	REMARK



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	07/29/22			
CHECKED BY:	DATE	FINISH	MODLE	SLIDE SWITCH
Jacky Chen	07/29/22			
APPROVED BY:	DATE	SCALE	DWG NO.	SS-12F20-Gx-S191
Tony Kao	07/29/22	1 : 1		
		SHEET NO.	PART NO.	SS-12F20-Gx-S191
		1 of 1		