



| | |
|--------------------------|--------|
| (Number of Conductors) N | X |
| (Pitch) P | 0.50mm |
| (Total Pitch) Pt | X |
| (Total Length) L | X |
| (Film Length) IL | X |
| (Margin Width) M | X |
| (Total Width) W | X |
| (Strip Length) S1 | X |
| (Strip Length) S2 | X |
| (Stiffener) B1 | X |
| (Stiffener) B2 | X |
| (Slanting) A1 | X |
| (Slanting) A2 | X |
| (Terminal thickness) t | X |
| (Thickness) T | X |

| | | | |
|-----------|--|--------------------------------|--------------|
| 規格 (Spec) | 0.5×X×X×B1 (X/X/X) (0.035×0.65) (0.06+0.06)UL20624 | | |
| 4 | 補強板 (Connecting) | 0.250 (深藍色) | |
| 3 | 上絕緣膠 (Top Insulation) | 0.06(白/印字 white/printed) 無鹵素皮膜 | 白色絕緣膠 / 綠色印字 |
| 2 | 下絕緣膠 (Under Insulation) | 0.06 (白white)無鹵素皮膜 | |
| 1 | 導體 (Conductor) | 0.035×0.65 (鍍錫Tin Plating) | |
| ITEM | DESCRIPTION | SPECIFICATION | REMARK |

| | | | |
|----------|-------------|-------|------|
| ITEM NO. | DESCRIPTION | DRAWN | DATE |
| | | | |
| | | | |
| | | | |
| | | | |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD. ANGEL'S



UNITS MM

| | |
|--------------|----------|
| DRAWN BY: | DATE |
| Jack Lu | 11/27/15 |
| CHECKED BY: | DATE |
| Jacky Chen | 11/27/15 |
| APPROVED BY: | DATE |
| Tony Kao | 11/27/15 |

| | | |
|-----------|----------|---------------|
| MAT'L | TITLE | FFC CABLE |
| FINISH | MODLE | FFC CABLE |
| SCALE | DWG NO. | FB11-xxx-S281 |
| SHEET NO. | PART NO. | FB11-xxx-S281 |
| SIZE | A4 | |
| VER | R | |