


DC MATE PLUG



P.C.B LAYOUT MOUNTING PATTERN (TOP VIEW)

MODEL NO.	DC-093HS
SCHEMATIC	4 (V+)
	3
	1(S)
	2(V-)

*MATERIAL

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : PHOSPHOR BRONZE
- TERMINAL 4 : PHOSPHOR BRONZE
- SPRING : STAINLESS STEEL
- SHIELD : BRASS
- HOUSING : PA6T

SPECIFICATION

1. Rating : DC 20V 8.0A
2. Contact resistance : ≤50mΩ
3. Insulation resistance : ≥100MΩ
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

1	新增SPEC	Jack	081214
ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	08/12/14			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	08/12/14			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-093HS-0.6
Tony Kao	08/12/14	1 : 1		
		SHEET NO.	PART NO.	DC-093HS-0.6
		1 of 1		
				SIZE A4
				VER R1