









P. C. B LAYOUT
TOP VIEW



ø2.50mm 3 POLE PLUG



SPECIFICATION

1. Rating : DC 30V 0.5A
2. Contact resistance : $\leq 30m\Omega$
3. Insulation resistance : $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

⑥	AXIS SUPPORT	1	BRASS	Ni-Plating
⑤	HOUSING	1	PBT	
④	4# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
③	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
②	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
①	1# CONTACT FOOT	1	PHOSPHOR BRONZE	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MATL	TITLE	JACK
Jack Lu	07/18/19			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	07/18/19			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-255-S124
Tony Kao	07/18/19	1 : 1	PART NO.	PJ-255-S124
		SHEET NO.	1 of 1	
				SIZE A4
				VER R1