






P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATION

- 1.Rating : DC 30V 0.5A ;
- 2.Contact resistance : $\leq 30\text{m}\Omega$;
- 3.Insulation resistance : $\geq 100\text{M}\Omega$ (DC250V) ;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles °

MODEL NO.	PJ-D2016-S187
SCHEMATIC	

4	HOUSING	1	PA66(Black)	
3	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating
2	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating
1	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°
3RD. ANGEL'S
UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	03/15/13			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	03/15/13			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-D2016-S187
Tony Kao	03/15/13	1 : 1		
		SHEET NO.	PART NO.	PJ-D2016-S187