










P.C.B LAYOUT
BOTTOM VIEW



SCHEMATIC (NON-SHORTING)




| Model No. | X(mm) |
|---|---|
| SK-22D06-G2 | 2mm |
| SK-22D06-G3 | 3mm |
| SK-22D06-G4 | 4mm |
| SK-22D06-G5 | 5mm |
| SK-22D06-G6 | 6mm |
| SK-22D06-G7 | 7mm |
| SK-22D06-G8 | 8mm |
| SK-22D06-G9 | 9mm |

SPECIFICATIONS

| | |
|---|---|
| Rating | 0.3A 50V DC |
| FUNCTION | 2P2T |
| Contact Resistance | 200mΩ Max. |
| Insulation Resistance | 100MΩ Min. |
| Operating Force | 350gf ± 100gf |
| Operating Life | 10,000 cycle |

| NO. | PARTS | MATERIALS | Q'TY | FINISH |
|---|---|---|---|---|
| 6 | CONTACT CLIP | PBS | 2 | NATURAL |
| 5 | SPRING PLATE | SUS | 1 | NATURAL |
| 4 | TERMINAL | BRASS | 6 | Ag PLATED |
| 3 | BASE | PHENOLIC RESIN | 1 | NATURAL |
| 2 | KNOB | POM | 1 | BLACK |
| 1 | FRAME | SPCC | 1 | Ni PLATED |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|---|---|---|---|
| 1 | 新增SPEC | Jack | 102215 |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

| | | | |
|---|---|---|---|
| DRAWN BY: Jack Lu | DATE 10/22/15 | MAT'L | |
| CHECKED BY: Jacky Chen | DATE 10/22/15 | FINISH | |
| APPROVED BY: Tony Kao | DATE 10/22/15 | SCALE 1 : 1 | SHEET NO. 1 of 1 |

| | | | |
|---|---|---|---|
| TITLE | SWITCH | | |
| MODLE | SLIDE SWITCH | | |
| DWG NO. | SK-22D06-Gx-S191 | SIZE | A4 |
| PART NO. | SK-22D06-Gx-S191 | VER | R1 |