






Model No.	X(mm)
SS-22D03-G2	2mm
SS-22D03-G3	3mm
SS-22D03-G4	4mm
SS-22D03-G5	5mm
SS-22D03-G6	6mm
SS-22D03-G7	7mm
SS-22D03-G8	8mm
SS-22D03-G9	9mm

SPECIFICATIONS

Rating	DC 50V 0.5A
Circuit	2P - 2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	250gf ±100gf
Operating Life (cycles)	10,000

6	SPRING PLATE	1	PBS	Natural
5	CONTACT CLIP	2	PBS	Ag-Plated
4	TERMINAL	6	BRASS	Ag-Plated
3	BASE	1	PHENOLIC RESIN	Natural
2	FRAME	1	SPCC	Ni-Plated
1	KNOB	1	POM	Black
NO.	DESCRIPTION	QTY	MATERIAL	REMARK

DRAWN BY:	DATE	MAT'L		TITLE	SWITCH	
Jack Lu	11/20/14					
CHECKED BY:	DATE	FINISH		MODLE	SLIDE SWITCH	
Jacky Chen	11/20/14					
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	SS-22D03-Gx-S191	SIZE A4
Tony Kao	11/20/14	SHEET NO.	1 of 1	PART NO.	SS-22D03-Gx-S191	VER A1

7	4	新增SPEC	Jack 112014
	3	更新為A0版	Jack 040814
	2	更新圖面	Jack 022514
	1	更新材質	Jack 091813
	ITEM NO.	DESCRIPTION	DRAWN DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5	±0.2	3RD. ANGEL'S		UNITS	MM
	Above 5 ~ 15	±0.3				
	Above 15 ~ 30	±0.4				
	Above 30 ~ 50	±0.5				
	Angle	±0.3°				