

RoHS Compliant


DIMENSIONS





SCHEMATIC



P.C.B MOUNTING PATTERN







Model No.	X(mm)
SS-22F07-G2	2mm
SS-22F07-G3	3mm
SS-22F07-G4	4mm
SS-22F07-G5	5mm
SS-22F07-G6	6mm
SS-22F07-G7	7mm
SS-22F07-G8	8mm
SS-22F07-G9	9mm
SS-22F07-G10	10mm
SS-22F07-G11	11mm
SS-22F07-G12	12mm
SS-22F07-G13	13mm

SPECIFICATIONS

Rating	DC 50V 0.5A
Circuit	2P - 2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	200gf ±80gf
Operating Life (cycles)	10,000

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	SPRING	2	STAINLESS STEEL	Natural
5	CONTACT	2	BRASS	Ag-Plated
4	TERMINAL	6	BRASS	Ag-Plated
3	BASE	1	PHENOLIC RESIN	Black
2	FRAME	1	SPCC	Ni-Plated
1	KNOB	1	POM	Black

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPPEC	Jack	112014
1	高度選項新增及更新尺寸及材質	Jack	041614

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 11/20/14	MAT'L	
CHECKED BY: Jacky Chen	DATE 11/20/14	FINISH	
APPROVED BY: Tony Kao	DATE 11/20/14	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	SLIDE SWITCH		
DWG NO.	SS-22F07-Gx-S191	SIZE	A4
PART NO.	SS-22F07-Gx-S191	VER	R2