



Model No.	X(mm)
SS-12D11-GA3	3mm
SS-12D11-GA4	4mm
SS-12D11-GA5	5mm
SS-12D11-GA6	6mm
SS-12D11-GA7	7mm
SS-12D11-GA8	8mm
SS-12D11-GA9	9mm
SS-12D11-GA10	10mm

SPECIFICATIONS

- 1.RATING: 50V AC , 0.5A
- 2.CONTACT RESISTANCE: 200 mΩ Max
- 3.INSULATION RESISTANCE: 100 MΩ Min
- 4.OPERATING FORCE: 250 ± 100gf
- 5.LIFE:10,000 CYCLES

NO.	PARTS	MATERIALS	Q'TY	FINISH
7	STEEL BALL	STEEL	1	NATURAL
6	SPRING	STEEL WIRE	1	NATURAL
5	CONTACT	BRASS	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	CASE	PA9T	1	BLACK
2	COVER	SUS	1	NATURAL
1	KNOB	PA9T	1	BLACK

ITEM NO.	DESCRIPTION	DRAWN	DATE
10	新增PCB LAYOUT尺寸	Jack	091125
9	更新尺寸	Jack	110122
8	更新柄長選項	Jack	011420
7	新增PCB LAYOUT尺寸	Jack	010319

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5	±0.2	3RD. ANGEL'S	UNITS	MM
Above 5 ~ 15	±0.3			
Above 15 ~ 30	±0.4			
Above 30 ~ 50	±0.5			

Angle ±0.3°

DRAWN BY:	DATE	MAT'L	TITLE	SIZE
Jack Lu	09/11/25	FINISH	MODLE	A4
CHECKED BY:	DATE	SCALE	DWG NO.	VER
Jacky Chen	09/11/25	1 : 1	SS-12D11-GAx-S191	R10
APPROVED BY:	DATE	SHEET NO.	PART NO.	
Tony Kao	09/11/25	1 of 1	SS-12D11-GAx-S191	