







P.C.B LAYOUT
TOP VIEW



SCHEMATIC



SPECIFICATION

- 1.Rating : DC 30V 1.0A ;
- 2.Contact resistance : $\leq 30m\Omega$;
- 3.Insulation resistance : $\geq 100M\Omega$;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-20N;
- 6.life test : 5,000 cycles °

4	PIN	1	PHOSPHOR BRONZE	Ag-Plating
3	SPRING	1	SUS	Ag-Plating
2	FLAT PIECE	1	BRASS	Ag-Plating
1	HOUSING	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	03/13/17	FINISH	MODLE	DC JACK
CHECKED BY:	DATE	SCALE	DWG NO.	DC-027-0.65-S124
Jacky Chen	03/13/17	SHEET NO.	PART NO.	DC-027-0.65-S124
APPROVED BY:	DATE			
Tony Kao	03/13/17			

1	新增剖面圖	Jack	031317
ITEM NO.	DESCRIPTION	DRAWN	DATE