



DC MATE PLUG

MODEL NO.	DC-068DS
SCHEMATIC	
CENTER PIN	ø1.65mm

***MATERIAL**

- TERMINAL 1 : BRASS
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : BRASS
- SHIELD : PHOSPHOR BRONZE
- COVER : PA6T

SPECIFICATION

1. Rating : DC 16V 2.5A
2. Contact resistance : ≤50mΩ
3. Insulation resistance : ≥100MΩ
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao

DATE: 08/11/14
 DATE: 08/11/14
 DATE: 08/11/14

MAT'L		TITLE	JACK
FINISH		MODLE	DC JACK
SCALE	1 : 1	DWG NO.	DC-068DS
SHEET NO.	1 of 1	PART NO.	DC-068DS
		SIZE	A4
		VER	A1

1	新增SPEC	Jack	081114
ITEM NO.	DESCRIPTION	DRAWN	DATE