








P.C.B LAYOUT MOUNTING PATTERN (TOP VIEW)

SPECIFICATION

- 1.Rating : DC 30V 0.5A
- 2.Contact resistance : $\leq 30\text{m}\Omega$
- 3.Insulation resistance : $\geq 100\text{M}\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-20N
- 6.life test : 5,000 cycles



Ø2.50mm 3 POLE PLUG



SCHEMATIC

PJ-2574	PJ-2573	PJ-2573A

5	HOUSING	1	PA9T	
4	CURVE PIECE	1	BRASS	Ag-Plating
3	SPRING	1	PHOSPHOR BRONZE	Ag-Plating
2	SPRING	1	PHOSPHOR BRONZE	Ag-Plating
1	SPRING	1	PHOSPHOR BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	04/23/21			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	04/23/21			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-257x-S124
Tony Kao	04/23/21	1 : 1		
		SHEET NO.	PART NO.	PJ-257x-S124
		1 of 1		

SIZE
A4
VER
R1