











P.C.B LAYOUT MOUNTING PATTERN
(TOP VIEW)



ø3.50mm 3 POLE PLUG





SPECIFICATION

1.Rating ：DC 30V , 0.5A；
2.Contact resistance：≤ 30mΩ ；
3.Insulation resistance：≥100MΩ ；
4.Withstand voltage：500VAC ；
5.Insertion and extraction force：3-20N
6.life test：5,000 cycles。

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	HOUSING	1	PBT	
5	CONTACT FOOT #5	1	Phosphor Bronze	Sn-Plating
4	CONTACT FOOT #4	1	Brass	Sn-Plating
3	CONTACT FOOT #3	1	Brass	Sn-Plating
2	CONTACT FOOT #2	1	Stainless Steel	Sn-Plating
1	CONTACT FOOT #1	1	Phosphor Bronze	Sn-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新圖面和料號	Jack	041222
1	更新plug圖	Jack	052418

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ± 0.2; Above 5 ~ 15 ± 0.3; Above 15 ~ 30 ± 0.4; Above 30 ~ 50 ± 0.5; Angle ± 0.3°
3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 04/12/22	MAT'L	
CHECKED BY: Jacky Chen	DATE 04/12/22	FINISH	
APPROVED BY: Tony Kao	DATE 04/12/22	SCALE	1 : 1
		SHEET NO.	1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-3615-S124	SIZE	A4
PART NO.	PJ-3615-S124	VER	R2