








P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

1.Electrical:

- 1.1 Contact resistance : 50m Ω max.
- 1.2 Dielectric withstanding voltage : 250 V RMS.
- 1.3 Insulation resistance : 50M Ω min.

2.Mechanical:

- 2.1 Mate and unmate force:
 - 2.1.1 Mate force : 3.0kg MAX
 - 2.1.2 Unmate force : 1.02kg MIN
- 2.2 Durability : 3,000 cycles MIN.

3.Environment:

Operating Temperature : -20°C to +85°C.

4.Material:

Housing: LCP,Black
Contact: Phosphor Bronze
Shell: SUS304

5.Plating Layer:

Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
Shell: Tin under Plated surface layer



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 12/18/13
DATE: 12/18/13
DATE: 12/18/13

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
MODLE
DWG NO.
PART NO.

CONNECTOR
MICRO USB AB TYPE 180 度直插 無捲邊
MRUSB-5AB-V2-S129
MRUSB-5AB-V2-S129

SIZE
A4
VER
R1

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新外觀材質	Jack	121813